Product Information HD DIESEL 10W30



Description

HD DIESEL 10W30 is a high-performance diesel engine oil formulated with high-quality mineral base oils and premium additives. It delivers exceptional protection and performance for vehicles operating under demanding conditions, including both on-road and off-road applications.

Applications

- Suitable for both light-duty and heavy-duty diesel-powered vehicles, including on-road and off- road applications.
- Designed to sustain engine durability in vehicles where exhaust gas recirculation (EGR) is used.

Specifications & Approvals

API CI-4, CH-4 ACEA E7-22 MTU Type 2 Volvo VDS-3 Cummin 20076/77 MAN 3275-1(Level) Mack EO-N

Features & Benefits

- Wear Protection: Provides superior protection against engine wear, extending engine life.
- Oxidation Stability: Extends oil life by resisting oil breakdown in high-temperature environments.
- Soot Control: Manages soot effectively, especially in engines with EGR systems.
- Cleanliness: Advanced detergents and dispersants prevent deposits and sludge.
- Fuel Efficiency: Improves fuel economy and lowers emissions.

Typical Properties

Properties	Test Method	Typical value
Appearance	Visual	Bright & Clear
ASTM Color	ASTM D1500/D6045	2.5
Density @15 °C	ASTM D4052	0.8677
Kinematic Viscosity @40 °C	ASTM D445	80.43
Kinematic Viscosity @100 °C	ASTM D445	11.65
Viscosity Index	ASTM D2270	137
Flash Point, COC	ASTM D92	230
Pour Point	ASTM D5950/D6892	-42
Total Base Number	ASTM D2896	9.1
Cold Cranking Simulator@-25 °C	ASTM D5293	6,543