



Product Information

SCOOTER HIGH TECH 10W40

Description

SCOOTER HIGH TECH 10W40 is a superior performance product formulated with a synthetic blend and high-quality additives that improve lubricity and friction control with fuel saving properties. It will help keep engines running clean protection even in extreme operating conditions and to provide reliable protection excellent engine cleanliness, prevent sludge, reduce wear, soot handling properties, oxidation stability.

Applications

- Recommended for dry-clutch scooters and automatic transmission motorcycles with or without catalytic converters.
- Suitable for all type of gasoline and ethanol blends.

Specifications & Approvals

JASO MB
API SL

Features & Benefits

- Excellent engine cleanliness, reduce deposit and oxidation control.
- Excellent oxidation stability, control viscosity increase and deposit formation.
- Reduces wear in severe operating conditions.
- Distinguished sludge control.
- Excellent to extend engine life.
- Reduces engine friction, improves mechanical efficiency
- Contributing to fuel economy and reduced emission.
- Engine oil flow easily when start-up at low temperature.
- Ideal for stop-and-go traffic.

Typical Properties

Properties	Test Method	Typical value
Appearance	Visual	Bright & Clear
ASTM Color	ASTM D1500	1.5
Density @15°C, g/cm ³	ASTM D4052	0.8628
Kinematic Viscosity @40°C, cSt	ASTM D445	100.7
Kinematic Viscosity @100°C, cSt	ASTM D445	14.66
Viscosity Index	ASTM D2270	151
Flash Point by COC, °C	ASTM D92	238
Pour Point, °C	ASTM D5950/6892/6749	-33
Cold Cranking Simulator @ -25°C, mPas	ASTM D5293	5,750
Total Base Number, mgKOH/g	ASTM D2896	6.21