

# Product Information

## XTEND SUV 5W30



### Description

XTEND SUV 5W30 is a premium synthetic motor oil that works hard to help keep engines clean and protected. It helps gasoline engine exhaust catalysts and keeps diesel particulate filters clean and protects it from ash build-up that can block the exhaust system and lead to reduced engine performance.

### Applications

- Suitable for modern gasoline engines, diesel engines with aftertreatment devices (GPF/DPF/TWC) and gas engines.
- Suitable for use with biodiesel and gasoline/ethanol blends.
- Engine oil with Mid SAPS-Level, intended for use as catalyst compatible oil at extended drain intervals in vehicles with all types of modern aftertreatment system and high-performance passenger car & light duty van gasoline & DI diesel engines.

### Specifications & Approvals

API SP  
ACEA C2-21, C3-21  
Daimler MB 229.31/229.51/229.52

### Features & Benefits

- Low Speed Pre-ignition (LSPI) reduction for engine durability
- Increase the DPF/GPF and TWC life and maintain the Vehicle's Fuel Economy
- Protects Turbocharged gasoline direct injection (T-GDI) engines and protection engine part
- Reduces oil consumption
- Excellent protection sludge and deposit, keep clean and prolong engine life
- Exceptional piston cleanliness, help prevent blow by and maintains engine power
- Outstanding wear protection, help improve fuel efficiency and maximize engine life

### Typical Properties

Properties	Test Method	Typical value
Appearance	Visual	Bright & Clear
ASTM Color	ASTM D1500	L3.0
Kinematic Viscosity @40°C, cSt	ASTM D445	71.44
Kinematic Viscosity @100°C, cSt	ASTM D445	12.03
Viscosity Index	ASTM D2270	166
Flash Point by COC, °C	ASTM D92	234
Pour Point, °C	ASTM D5950/6892/6749	-42
Total Base Number, mgKOH/g	ASTM D2896	6.9
Sulphated ash, %	ASTM D874	0.65
Cold Cranking Simulator @-30 °C, mPas	ASTM D5293	6,230